

Rec'd PCT/PTO 08 MAR 2005

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/527043



(43) International Publication Date
25 March 2004 (25.03.2004)

PCT

(10) International Publication Number
WO 2004/025800 A3

(51) International Patent Classification⁷: H01M 8/10

G. [US/US]; 16 Pierson's Ridge, Hockessin, DE 19707 (US).

(21) International Application Number:
PCT/US2003/029160

(74) Agent: FICKES, Daphne, P.; E.I. Du Pont De Nemours And Company, Legal Patent Records Center, 4417 Lancaster Pike, Wilmington, DE 19805 (US).

(22) International Filing Date:
12 September 2003 (12.09.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/410,766 13 September 2002 (13.09.2002) US

(71) Applicant (*for all designated States except US*): E.I. DU PONT DE NEMOURS AND COMPANY [US/US]; 1007 Market Street, Wilmington, DE 19898 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): RAJENDRAN, Raj,

[Continued on next page]

(54) Title: MEMBRANES FOR FUEL CELLS



(57) Abstract: The invention provides a direct methanol fuel cell comprising: (a) a solid fluorinated polymer electrolyte membrane having an ion exchange ratio (IXR) of at least about 17, wherein the solid polymer electrolyte membrane has a first surface and a second surface; and (b) at least one catalyst layer present on each of the first and second surfaces of the solid polymer electrolyte membrane; wherein the fuel cell is operated at a temperature of less than 60 °C; and wherein the methanol cross-over rate is reduced by at least about 20 %; and the power output is equal to or increased up to about 15%, versus a fuel cell comprising a solid fluorinated polymer electrolyte membrane having the same thickness, and an ion exchange ratio (IXR) of about 15.

WO 2004/025800 A3